

E228 Steel

Hybrid stove E228 STEEL, the practicality of pellets and the crackling sound of wood, combined to offer the utmost advantages. Modern design, featuring sober and rigorous lines. Entirely clad with large-size steel panels revealing a finely worked finish. Available in different colors.



GENERAL FEATURES

- Hybrid wood-pellet stove with natural draught: yes
- Automatic switching wood-pellet/pellet-wood: yes
- Heating: Natural convection / Ductable forced ventilation
- Natural Mode: yes
- Pellet Quality System Function: yes
- Eco / Energy Saving function: yes / yes
- Timer-controlled thermostat with programming: 6 daily time frames
- Cladding / Top: steel / steel
- One-piece firebox: airtight in steel
- Firebox: Aluker®
- Door / Handle: cast iron with ceramic glass resistant to 750°C / steel and silicone
- Flue gas deflector / Brazier: Aluker® / cast iron
- Raised pellet brazier: yes
- Power levels: 5
- Double auger with bottom feeding: yes
- Control panel with digital controls: yes
- Cyclic brazier cleaning: yes
- Glass cleaning: continuous air flow
- Installation: flush with the wall - corner
- Warning system in case of abnormal pellet tank and door opening: yes
- Wood re-load warning: yes
- Flue malfunction detection sensor: yes
- Tertiary air system in pellet mode: yes
- Controlled unlocking system of pellet tank and door: yes
- Ambient probe for temperature control: as standard feature
- Remote control with LCD display:
- Humidifier: stainless steel
- Front ventilation: adjustable vent
- Multifuco System®: with 4 speed levels, manually or automatically controlled, optional
- Module WiFi - Bluetooth for MyPiazzetta App: standard
- Ash vacuum cleaner: as standard feature
- Removable ash pan: yes
- Pellet level indicator: on remote control
- Multicomfort / Multicomfort Plus: standard
- Standard flue outlet position: top or rear

TECHNICAL DETAILS

- Model E228 ST
- Rated efficiency power % 88,0
- Efficiency - min power % 90,3
- Rated output max kW 8,2
- Rated output min kW 4,1
- Rated consumption max kg/h 1,9
- Rated consumption min kg/h 0,9
- Dimensions D cm 59
- Dimensions W cm 60
- Dimensions H cm 142
- Weight kg 240

COVERS

