P930 K

P930 K

A pellet stove offering a striking visual impact, characterized by refined processing and by its majolica decorations. Designed with a square-shaped cross-section revealing soft and rounded lines. The hot air outlet can be arranged on the side.

The P930 K features an aesthetic steel door to give continuity to its Majolica cladding, the Multicomfort to manage temperature with maximum comfort thanks to the remote control with thermostat, and a cast-iron firebox that ensures a long product life. With its 11 kW it is the ideal stove for heating rooms up to 110 m2. Discover all the colours and features.





GENERAL FEATURES

- ·Heating: Multifuoco System® with 4 power levels and manual or automatic control. Hot ductable air
- ·Natural Mode: yes
- •Power levels: 5
- •Radiant Majolica: yes
- •Dual Power System: 4 power levels and manual or automatic control
- Cladding / Top: majolica / steel cast iron
 Front ventilation: adjustable vent
- •Humidifier: stainless steel
- •Remote control with LCD display:
- ·Multicomfort: standard
- ·Multicomfort Plus: standard
- •Ambient probe for temperature control: as standard feature
- ·Control panel with digital controls: yes ·Module WiFi - Bluetooth for MyPiazzetta App: standard
- ·Wireless probe for temperature management: optional
- •Timer-controlled thermostat with programming: 6 daily time frames

- Eco / Energy Saving function: yes / yes
 Glass cleaning: continuous air flow
 Cyclic brazier cleaning: yes
 Ash vacuum cleaner: as standard feature
- •Installation: flush with the wall corner •Standard flue outlet position: left rear or upper
- One-piece firebox: airtight in steel
- ·Firebox: cast iron
- •Door / Handle: cast iron with ceramic glass resistant up to 750°C / detachable
- •Combustion air kit:
- ·Design door:
- ·Air Combustion System Function: yes
- •Pellet Quality System Function: yes
- ·Ash conveyor: steel
- ·Side ventilation: optional vent, fixed
- ·Combustion air kit:

TECHNICAL DETAILS

- •Rated thermal power (min max) kW 3,9 11,0 •Efficiency (min max) % 90,0 90,7
- Energy efficiency class A+
- •Rated consumption (min max) kg/h 0,8 2,4
- Tank capacity kg 26
- •Weight kg 187 •Standard flue outlet Ø cm 8
- •Model P930 K

COVERS















