P985 TH

Extremely compact design for this Thermo pellet stove of just 32 cm. Cladded with a large-sized front panel of Majolica: Bianco, Ardesia, Canapa, Grigio Cerato, Rosso Lava and Terra Oriente. Top part in Majolica including the Rolling top system for easy topping up with pellets. Perfect for being installed in corridors.



GENERAL FEATURES

- ·Heating: hot water production
- Cladding: majolica
- Rolling Top: sliding top
- Top: majolica
- One-piece firebox: steel
- ·Boiler: steel
- •Firebox: steel Aluker®
- ·Fume deflector: steel
- ·Ash conveyor: steel
- ·Exchanger cleaning: rotor cleaning system, Patented
- •Brazier: cast iron
- •Expansion tank: as standard feature •Standard circulator pump: high efficiency
- •Safety valve and relief valve: as standard feature
- •Door: steel cast iron with ceramic glass resistant to 750°C
- ·Handle: steel with nickel-plated finish
- •Standard flue outlet position: RH rear RH side RH top
- ·Remote control with LCD display: yes
- ·Function control: control panel with digital controls
- •Power adjustment: automatic with 16 levels depending on the set temperature
- •Timer-controlled thermostat with programming: 6 daily time frames
- •Ceramic glass: resistant to 750°C
- ·Glass cleaning: continuous air flow
- •Cyclic brazier cleaning: yes
- •Energy Saving: yes
 •Eco Function: yes
- •Frost Function: yes
- •Probe for managing storage tank: as standard feature •Probe for managing DHW storage tank: as standard feature
- •Can be connected to an external thermostat: yes
- ·AUX control: yes
- ·Ash vacuum cleaner: as standard feature
- ·Electronically-controlled anti-condensation valve: optional
- ·Installation: wall flush with the corner
- ·Flush with the wall installation: yes
- ·Combustion air kit: optional

TECHNICAL DETAILS

- •Energy efficiency class A+
- •Rated thermal power (min max) kW 5,6 13,2
- Efficiency (min max) % 91,4 92,5
- Max operating pressure bar 1.5
- 3-bar safety discharge valve Ø 1/2"
- Heat system delivery Ø 3/4"
- •Heat system return Ø 3/4"
- •Rated consumption (min max) kg/h 1,2 2,9
- Weight kg 215
- ·Standard flue outlet Ø cm 8
- •Model P985 TH

COVERS















8 cm 6 cm S R

