

ME 90



GENERAL FEATURES

- Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: enamelled steel door with self-cleaning ceramic glass resistant up to 750°C. Drop down opening for easy cleaning
- Door profile: for flush dry wall installation, in painted steel 12 cm depth
- Handle: in painted steel, removable
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: manual valve opening with console on firebox
- Standard flue outlet position: top
- Fuel: wood
- Combustion air kit: optional

TECHNICAL DETAILS

- Energy efficiency class A+ (G → A++)
- Rated output max kW 14,0
- Rated efficiency power % 86,0
- Rated consumption max kg/h 4,0
- Vertically sliding opening cm 30
- Firebox opening (W) - Dimensions for the passage of wood cm 89
- Firebox opening (H) - Dimensions for the passage of wood cm 22,5
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 90,5
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 44
- Weight kg 295
- Model ME 90

