## **ME 90 B**



## **GENERAL FEATURES**

- ·Heating: natural convection, radiation or optional ductable forced ventilation with the Multifuoco System® or Multifuoco System Plus,
- Structure: coated steel with closed firebox
- •Firebox: Aluker®
- •Hearth: cast iron
- ·Hood: steel
- •Door profile: for flush dry wall installation, in painted steel 12 cm depth
- •Handle: in painted steel, removable
- •Primary air: manually adjustable
- Secondary air: pre-determined
- •Flue gas adjustment: manual valve opening with console on firebox
- ·Standard flue outlet position: top
- •Fuel: wood

## **TECHNICAL DETAILS**

- •Energy efficiency class  $A+(G \rightarrow A++)$
- •Rated output max kW 15,0

- Rated output max kW 15,0

  Rated efficiency power % 82,5

  Rated consumption max kg/h 4,5

  Vertically sliding opening cm 30

  Firebox opening (W) Dimensions for the passage of wood cm 89

  Firebox opening (H) Dimensions for the passage of wood cm 22,5
- •Mouth of firebox (W) Minimum dimensions of mouth of cladding cm 90,5
- •Mouth of firebox (H) Minimum dimensions of mouth of cladding cm 44
- ·Weight kg 275
- •Model ME 90 B



