ME 90 D/S



GENERAL FEATURES

- ·Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
 •Structure: coated steel with closed firebox
- •Firebox: Aluker® Hearth: cast ironHood: steel
- *Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Rise n'fall door for wood loading, hinged opening for cleaning
- •Door profile: for flush dry wall installation, in painted steel 12 cm depth
- ·Handle: in painted steel, removable
- ·Primary air: manually adjustable
- Secondary air: pre-determined
- •Flue gas adjustment: manual valve opening with console on firebox
- Standard flue outlet position: top
- ·Fuel: wood
- •Combustion air kit: optional

TECHNICAL DETAILS

- •Energy efficiency class A+ (G \rightarrow A++)
- •Rated output max kW 16,0
- •Rated efficiency power % 81,0
- ·Rated consumption max kg/h 4,8
- Vertically sliding opening cm 32
 Firebox opening (W) Dimensions for the passage of wood cm 78,5
- •Firebox opening (H) Dimensions for the passage of wood cm 24,5
- •Mouth of firebox (W) Minimum dimensions of mouth of cladding •Mouth of firebox (D) - Minimum dimensions of mouth of cladding
- cm 61 •Mouth of firebox (H) - Minimum dimensions of mouth of cladding
- cm 51 ·Weight kg 330
- •Model ME 90 D



