ME 90



GENERAL FEATURES

- ·Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
 •Structure: coated steel with closed firebox
- •Firebox: Aluker®
- Hearth: cast ironHood: steel
- *Opening: enamelled steel door with self-cleaning ceramic glass resistant up to 750°C. Drop down opening for easy cleaning
- •Door profile: for flush dry wall installation, in painted steel 12 cm depth
- ·Handle: in painted steel, removable
- ·Primary air: manually adjustable
- Secondary air: pre-determined
- •Flue gas adjustment: manual valve opening with console on firebox
- ·Standard flue outlet position: top
- ·Fuel: wood
- Combustion air kit: optional

TECHNICAL DETAILS

- •Energy efficiency class $A+(G \rightarrow A++)$
- •Rated output max kW 14,0

- Rated output max kW 14,0

 Rated efficiency power % 86,0

 Rated consumption max kg/h 4,0

 Vertically sliding opening cm 30

 Firebox opening (W) Dimensions for the passage of wood cm 89

 Firebox opening (H) Dimensions for the passage of wood cm 22,5
- •Mouth of firebox (W) Minimum dimensions of mouth of cladding cm 90,5
- •Mouth of firebox (H) Minimum dimensions of mouth of cladding cm 44
- ·Weight kg 295
- •Model ME 90



